



# The Off-Fence Mortising Kit

13160 Saticoy St. N. Hollywood, CA 91605 Tel: 1-800-480-6427

Email: [microfence@microfence.com](mailto:microfence@microfence.com)

Website: [www.microfence.com](http://www.microfence.com)

The **Micro Fence Off-Fence Mortising Kit** has been designed to take optimum advantage of the Micro Fence's measuring capabilities in mortising operations with the hand-held router. The micrometer adjustment makes mortise and tenon joint tolerances simple, measurable and repeatable tasks.

The Off-Fence Kit provides an aluminum secondary fence that opposes the Micro Fence Edge Guide and "entraps" the work piece, making it virtually impossible to spoil the cut by wandering from the edge of the material, (even when making multiple passes). We have chosen to standardize this accessory to be fitted with our **Model A Mounting Bar** which is required for its use.

The kit includes:

- # 1 One Aluminum Off-Fence
- # 2 Two ¼ - 20 Locking Knobs
- # 3 Two 5/8" Stainless Steel Washers
- # 4 Two Lock Washers
- # 5 One Universal Router Plate
- # 6 One Centering Hub
- # 7 Two Pan Head Locking Screws
- # 8 Two Trimmer Posts
- # 9 Two Flat Head Locking Screws

Initial Assembly:

- a) Drill holes in the appropriate configuration to mount your router (see steps below) on the Universal Router Plate (#5).
- b) Install the UHMW tape on the ½" face of the aluminum Off Fence before use. It will maximize smooth travel on wooden surfaces.
- c) Install lock washers (#4), then the stainless flat washers (#3) on the locking knobs #2).
- d) Fasten the Trimmer Posts (#8) in the .045" deep counter-bored holes on the top of the Universal Router Plate and fasten from the bottom with the two flat head screws (#9).
- e) Install the two Pan Head Locking Screws (#7) in the top of each Trimmer Post .

